



# LOW PROFILE LED BEACONS

Dual 12/24V low profile flashing beacons

## FEATURES

- Dual 12V/24V dc models
- Red, Blue, Amber and Clear lens options
- IP66 rated
- Uses LED technology
- 1Hz flash rate
- Low current operation
- Fresnel Lens
- 3 year warranty

## BENEFITS

- Compatible with a wide range of systems
- Suitable for use in fire, intruder, access control systems or general applications
- Maximum light intensity and dispersion



## DESCRIPTION

Dual 12V/24V low profile flashing beacons utilising efficient LED technology for indoor and outdoor use.

## TECHNICAL SPECIFICATIONS

<b>Rate Voltage</b>	12V dc / 24V dc
<b>Current Consumption</b>	80mA - 12V dc 30mA - 24V dc
<b>Operating Temperature</b>	-10°C to 50°C
<b>Electrical Connection</b>	350mm flying lead
<b>Mounting</b>	Direct OR optional quick release base (provided)



## APPROVALS

ROHS Compliant  
UKCA | CE Mark

EL7M0045-2022-Issue1

## ORDERING INFORMATION

Lens Colour	Part Number	Fixing
<b>Amber</b> 	LPB1224-A-S	Single
	LPB1224-A-T	Twin
<b>Blue</b> 	LPB1224-B-S	Single
	LPB1224-B-T	Twin
<b>Clear</b> 	LPB1224-C-S	Single
	LPB1224-C-T	Twin
<b>Red</b> 	LPB1224-R-S	Single
	LPB1224-R-T	Twin